



Cirrus Heaters



Cirrus Soapstone
(CIR)



Cirrus Rock
(CRR)

Cirrus Heaters

Cirrus Soapstone is a heater with a stylish slim design. It represents modern heater technology that combines Finnish soapstones and traditional sauna rocks. The smart design of the heater and the uniquely designed soapstones with water pockets, assure that a larger surface area of rocks comes into contact with the water, releasing more steam evenly throughout the sauna room.

Cirrus Rock is a modified model of Cirrus Soapstone. With shorter safety distances the Cirrus Rock's robust design and stainless steel frame represent the new, trendy heaters with large volume of sauna rocks. Likewise Cirrus Soapstone, Cirrus Rock ensures that a larger surface area of rocks comes into contact with water, releasing more steam evenly in every direction.



Note: Sauna stones and decorative soapstone cubes are not included.

Model Name	Power (kW)	Sauna Room(m ³)		Supply Voltage	Fuse Size (Ampere)	Control	Heater Dimensions (mm)			Soapstones (kg)	Stones (kg)
		min	max				Width	Depth	Height		
CIR-30NB CRR-30NB	3.0	2	4	220-240V 1N~/ 380-415V 2N~	1 x 16 2 x 10	8+4h	360	220 265	910	20 —	5 30
CIR-40NB CRR-40NB	4.0	3	6	380-415V 2N~	2 x 10	8+4h	360	220 265	910	20 —	5 30
CIR-50NB CRR-50NB	5.0	4	8	380-415V 2N~	2 x 16	8+4h	360	220 265	910	20 —	5 30
CIR-45NB CRR-45NB	4.5	3	6	380-415V 3N~	3 x 10	8+4h	505	220 265	910	30 —	8 50
CIR-60NB CRR-60NB	6.0	5	8	380-415V 3N~	3 x 10	8+4h	505	220 265	910	30 —	8 50
CIR-75NB CRR-75NB	7.5	8	12	380-415V 3N~	3 x 16	8+4h	505	220 265	910	30 —	8 50
CIR-30NS CRR-30NS	3.0	2	4	220-240V 1N~/ 380-415V 2N~	1 x 16 2 x 10	separate	360	220 265	910	20 —	5 30
CIR-40NS CRR-40NS	4.0	3	6	220-240V 1N~/ 380-415V 2N~	1 x 20 2 x 10	separate	360	220 265	910	20 —	5 30
CIR-50NS CRR-50NS	5.0	4	8	220-240V 1N~/ 380-415V 2N~	1 x 25 2 x 16	separate	360	220 265	910	20 —	5 30
CIR-45NS CRR-45NS	4.5	3	6	380-415V 3N~	3 x 10	separate	505	220 265	910	30 —	8 50
CIR-60NS CRR-60NS	6.0	5	8	380-415V 3N~	3 x 10	separate	505	220 265	910	30 —	8 50
CIR-75NS CRR-75NS	7.5	8	12	380-415V 3N~	3 x 16	separate	505	220 265	910	30 —	8 50

